






















Peltier Thermoelectric Cooling Modules

TEC1-01708 TEC1-01708S	US\$4.45 US\$4.75	Size 15x15x3.7mm (WxDxH), weight 6g I _{max} 8.5A, U _{max} 2.0V, R = 0.21 ohm, 17 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 9.5W	
TEC1-03108	US\$5.19	Size 20x20x3.3mm (WxDxH), weight 8g I _{max} 8.5A, U _{max} 3.7V, R = 0.40 ohm, 31 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 17.6W	
TEC1-04908	US\$5.39	Size 25x25x3.7mm (WxDxH), weight 11g I _{max} 8.5A, U _{max} 5.9V, R = 0.57 ohm, 49 couples ΔT max. = 66°C, Q _{max} (ΔT =0) 30W	
TEC1-07103 TEC1-07103HTS	US\$6.39 US\$7.19	Size 30x30x4.7mm (WxDxH), weight 14g I _{max} 3.3A, U _{max} 8.5V, R = 1.94 ohm, 71 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 18.0W	
TEC1-07108 TEC1-07108S TEC1-07108HT	US\$5.89 US\$6.19 US\$6.69	Size 30x30x3.5mm (WxDxH), weight 17g I _{max} 8.5A, U _{max} 8.5V, R = 0.85 ohm, 71 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 40.0W	
TES1-12703 TES1-12703S	US\$5.89 US\$6.19	Size 30x30x3.3mm (WxDxH), weight 14g I _{max} 3.2A, U _{max} 15.4V, R = 3.85 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 30.0W	
TES1-12704 TES1-12704S	US\$5.89 US\$6.19	Size 30x30x3.3mm (WxDxH), weight 16g I _{max} 4.3A, U _{max} 15.4V, R = 3.10 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 40.0W	
TEC1-12703 TEC1-12703S TEC1-12703HT TEC1-12703HTS	US\$8.39 US\$8.69 US\$9.69 US\$9.99	Size 40x40x4.7mm (WxDxH), weight 31g I _{max} 3.3A, U _{max} 15.4V, R = 3.42 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 38.0W	

TEC1-12704	US\$6.29	Size 40x40x4.7mm (WxDxH), weight 31g I _{max} 4A, U _{max} 15.4V, R = 2.85 ohm, 127 couples ΔT max. = 66°C, Q _{max} (ΔT =0) 33.4 W	
TEC1-12705 TEC1-12705S TEC1-12705HT	US\$7.49 US\$7.79 US\$7.99	Size 40x40x4.0mm (WxDxH), weight 29g I _{max} 5.3A, U _{max} 15.4V, R = 2.20 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 57.0W	
TEC1-12706 TEC1-12706S TEC1-12706HTS	US\$7.49 US\$7.79 US\$7.99	Size 40x40x3.9mm (WxDxH), weight 27g I _{max} 6.4A, U _{max} 15.4V, R = 1.98 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 63.0W	
TEC1-12707 TEC1-12707HT TEC1-12707HTS	US\$7.49 US\$7.99 US\$8.29	Size 40x40x3.5mm (WxDxH), weight 25g I _{max} 7.4A, U _{max} 15.4V, R = 1.80 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 75.0W	
TEC1-12708 TEC1-12708S TEC1-12708HTS	US\$7.49 US\$7.79 US\$8.29	Size 40x40x3.5mm (WxDxH), weight 23g I _{max} 8.5A, U _{max} 15.4V, R = 1.55 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 85.0W	
TEC1-12710 TEC1-12710S TEC1-12710HT TEC1-12710HTS	US\$7.69 US\$7.99 US\$8.49 US\$8.79	Size 40x40x3.3mm (WxDxH), weight 26g I _{max} 10.5A, U _{max} 15.4V, R = 1.08 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 100.0W	
TEC1-12715 TEC1-12715S TEC1-12715HT TEC1-12715HTS	US\$25.89 US\$26.19 US\$27.49 US\$27.79	Size 50x50x3.9mm (WxDxH), weight 50g (Jumbo Junior) I _{max} 15.6A, U _{max} 15.4V, R = 0.80 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 150 W	
TEC1-26316	US\$39.99	Size 50x50x3.1mm (WxDxH), weight 65g (Jumbo Junior) I _{max} 16.0A, U _{max} 31.5V, R = 1.60 ohm, 263 couples ΔT max. = 66°C, Q _{max} (ΔT =0) 300 W	

TEC1-12730	US\$32.19	Size 62x62x3.9mm (WxDxH), weight 90g (Jumbo) I _{max} 30.7A, U _{max} 15.4V, R = 0.35 ohm, 127 couples ΔT max. = 68°C, Q _{max} (ΔT =0) 350 W	
TEC1-12730S	US\$32.49		
TEC1-12730HT	US\$35.49		
TEC1-12730HTS	US\$35.79		
TEC1-06306	US\$4.29	Size 40x20x3.9mm (WxDxH), weight 17g I _{max} 6A, U _{max} 7.6V, R = 0.95-1.05 ohm, 63 couples ΔT max. ≥ 63°C, Q _{max} (ΔT =0) 42W	
TEC1-06308	US\$4.29	Size 40x20x3.9mm (WxDxH), weight 17g I _{max} 8.5A, U _{max} 7.6V, R = 0.65-0.75 ohm, 63 couples ΔT max. ≥ 63°C, Q _{max} (ΔT =0) 32W	
TEC1-06310	US\$4.29	Size 40x20x3.3mm (WxDxH), weight 17g I _{max} 7.5A, U _{max} 7.5V, R = 0.55-0.65 ohm, 63 couples ΔT max. ≥ 63°C, Q _{max} (ΔT =0) 45W	
TEC1-06312	US\$4.59	Size 40x20x3.1mm (WxDxH), weight 17g I _{max} 9.5A, U _{max} 7.5V, R = 0.45-0.55 ohm, 63 couples ΔT max. ≥ 63°C, Q _{max} (ΔT =0) 55W	
TEC1-06315	US\$5.19	Size 40x20x3.1mm (WxDxH), weight 17g I _{max} 12.5A, U _{max} 7.6V, R = 0.3-0.4 ohm, 63 couples ΔT max. ≥ 63°C, Q _{max} (ΔT =0) 65W	